

CS - CONTRACTOR SERIES

Extended power handling

Phase Tech's CS Series offers extended performance and power handling for in-ceiling or in-wall applications. Each model features extra-high sensitivity to assure satisfying volume, even with low-powered distribution systems.

Acoustically superior

The CS Series is engineered to handle the dynamic range of multi-channel audio technologies like Dolby Digital and DTS and well as traditional two-channel sources. The CS Series delivers high-end tonal balance and a clear distinction between musical notes.

Durable performance

The line comprises two-way models including 5.25" or 6.5" polypropylene cones with butyl-rubber surrounds for lasting performance, indoors or out. Multiple tweeter configurations allow the CS Series to match the needs of any room.

CS-6R/PT



2-Way 6.5" woofer with .75" pivoting tweeter CS-6R/PT incorporates a .75" dome tweeter and 6.5" woofer, offering extended performance and power handling for outstanding reproduction of movies and music. The pivoting tweeter allows the speaker to be properly aimed at the listener in off-axis mounting situations.

CS-6R



2-Way 6.5" woofer with .75" fixed tweeter CS-6R incorporates a .75" dome tweeter and 6.5" woofer, offering excellent performance for all types of music and movies.

CS-5R



2-Way 5.25" woofer with .75" fixed tweeter CS-5R incorporates a .75" dome tweeter and 5.25" woofer, offering excellent performance in smaller spaces for all types of music and movies.

CS-650



2-Way in-wall 6.5" woofer with .75" tweeter All CS Series speakers are designed to handle the full dynamic range of today's multi-channel digital sources. The CS-650 includes a durable two-way weather-resistant design for use indoors or out when an in-wall application is needed.

CS-525



2-Way in-wall 5.25" woofer with .75" tweeter The CS-525 offers quality performance for smaller areas in a durable two-way weather-resistant design for use indoors or out.

CS-6DVR



2-Way 6.5" dual voice coil woofer with a dual .75" pivoting tweeter assembly CS-6DVR incorporates two .75" dome tweeters in a pivoting housing and 6.5" dual voice coil woofer, offering stereo sound from a single speaker for secondary listening areas. Included jumper switches also allow for use as a bipole or dipole surround speaker in a home theater system.

CS-5DVR



2-Way 5.25" dual voice coil woofer with a dual .75" pivoting tweeter assembly CS-5DVR incorporates two .75" dome tweeters in a pivoting housing and 5.25" dual voice coil woofer, offering stereo sound from a single speaker for smaller secondary listening areas. Included jumper switches also allow for use as a bipole or dipole surround speaker in a home theater system.



CS-6R/PT

Tweeter	.75" Aimable Dome
Woofer	6.5" Polypropylene /Butyl surround
Frequency	48 Hz - 20 kHz
Sensitivity	90 dB
Impedence	8 Ohms
Finish	White
Mounting Depth	3 1/2"
Inputs	Push Termial
Grilles	Perforated
Recomended Amp Power	5 - 100 Watts RMS
Cutout Dim.	7 5/8"
Outside Dim.	8 13/16"
Ship Weight	4.5 lbs



CS-6R

.75" Dome
6.5" Polypropylene /Butyl surround
48 Hz - 20 kHz
90 dB
8 Ohms
White
2 5/8"
Push Termial
Perforated
5 - 100 Watts RMS
8 1/8"
9 1/2"
3.5 lbs



CS-5R

.75" Dome
5.25" Polypropylene /Butyl surround
60 Hz - 20 kHz
90 dB
8 Ohms
White
2 3/8"
Push Termial
Perforated
5 - 80 Watts RMS
7"
8 3/8"
3 lbs



CS-5DVR

2 x .75" Aimable Dome
5.25" Polypropylene /Butyl surround
48 Hz - 20 kHz
90 dB
8 Ohms
White
3 1/2"
Bi/Dipole Switchable
Perforated
5 - 100 Watts RMS
6 7/8"
8 1/8"
3 lbs



CS-6DVR

2 x .75" Aimable Dome
6.5" Polypropylene /Butyl surround
48 Hz - 20 kHz
90 dB
8 Ohms
White
3 1/2"
Bi/Dipole Switchable
Perforated
5 - 100 Watts RMS
7 5/8"
8 13/16"
5 lbs



CS-650

2 x .75" dome
6.5" polypropylene
52 Hz - 20 kHz (3 dB)
90 dB
8 Ohms
3-1/8"
Push Termial
10 - 80 Watts RMS
6-3/4" (W) x 10-1/4" (H)
8" (W) x 11-3/4" (H)"
3 lbs



CS-525

2 x .75" dome
5.25" polypropylene
68 Hz - 20 kHz (3 dB)
90 dB
8 Ohms
3-1/8"
Push Termial
10 - 65 Watts RMS
6-3/4" (W) x 10-1/4" (H)"
8" (W) x 11-3/4" (H)"
3 lbs